

ProLite E2208HDS-1

The ProLite E2208HDS Widescreen LCD is the first to feature true High Definition, 16:9, 1920 x 1080 pixels as its native resolution. Impressive colour reproduction is achieved with a typical contrast ratio of 1000:1 with the User Option to enhance further with Advanced Contrast Ratio enabled for 10,000:1. Complimented by a blistering 5msec Response Time, makes the E2208HDS ideal for High Definition Video and Gaming applications. 'Opticolour' automatically makes calibrated adjustments to Contrast, Brightness and Colour Balance to suit your application needs. Analogue and Digital inputs guarantees flexible connectivity.



Panel	TN
Diagonal	22"
Display area h x w	268.1 x 476.64 mm
Response time	5 ms
Contrast	10000 : 1 ACR
Contrast ratio	1000 : 1 typical
Brightness	300 cd/m ² max.
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 85/75°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	1920 x 1080 (2.1 megapixel)
Horizontal sync	31 - 83 KHz
Vertical sync	56 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D signal cable, audio cable, user manual, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 10 languages (EN, FR, DE, IT, PL, ESP, NL, JP, Chinese, RU) and 6 front controls (Power, Menu /Select, Scroll up /Brightness, Scroll down /ECO, Exit /OptiColour, Auto)
User controls	auto adjust, brightness, contrast, geometry (H. position, V. position, pixel clock, phase), colour, OSD (H. position, V. position, OSD Time out), language, miscellaneous (sharpness, DDC/CI, display information, ACR, display mode), input select, audio (volume, mute), recall
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Ergonomics	TCO '03, ISO 13406-2
Safety	CE, TÜV-GS/MPR III, VCCI-B
Power supply	AC 100-240V, 50/60 Hz
Power Supply Unit	internal
Power usage	43 W typical; max. 2 W in Power management mode
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	516.5 x 386 x 193 mm
Weight	4.2 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.