

▶ 17" LCD DISPLAY

# E-17/E-17A (R12)



▶ FEATURES

- Exceptionally elegant exterior
- Stylish rear side design
- Swift 12ms response time
- High 260 brightness
- Crisp 450 contrast ratio
- NeoV Optical Glass™
- Built-in speakers with headphone jack
- Auto-adjustment for optimal setting
- Intuitive OSD with key lock function
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD	
	<b>Panel Size</b>	17.0" (432mm)	
	<b>Max. Resolution</b>	SXGA 1280 x 1024	
	<b>Pixel Pitch</b>	0.264mm	
	<b>Brightness</b>	260cd/m <sup>2</sup> (Typical)	
	<b>Contrast Ratio</b>	450:1 (Typical)	
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment	
	<b>Viewing Angle (H/V)</b>	150°/145° (Typical)	
	<b>Display Color</b>	16.7M	
	<b>Response Time</b>	12ms	
Input	<b>Frequency (H/V)</b>	H: 24kHz - 80kHz V: 50Hz - 75Hz	
	<b>Max. Pixel Clock</b>	135MHz	
	<b>Life Time</b>	50,000hrs (Minimum)	
Input	<b>Analog</b>	15-Pin D-Sub	
Audio	<b>Audio In</b>	3.5mm Audio Line-in	
	<b>Audio Out</b>	3.5mm Headphone Jack	
	<b>Speaker</b>	1W x 2	
Connector	<b>Power</b>	3-Pin AC Plug	
NeoV Optical Glass	<b>Thickness</b>	3.0mm (0.18")	
	<b>Reflection Rate</b>	<1%	
	<b>Transmission Rate</b>	>96%	
	<b>Hardness</b>	>6H (MOH's Rating)	
Tilt	<b>Tilt</b>	+5° ~ +25°	
Mounting	<b>VESA FPMPI</b>	Yes (100mm)	
Regulation Approval	<b>Safety &amp; EMI</b>	UL/CUL, TUV/BAURT, EPA, NORDIC, CB, TCO 95, FCC, CE, BSMI, VCCI, CCC, GOST	
	<b>VESA</b>	DDC 1/2B, DPMS	
Power	<b>Power AC Consumption</b>	100 - 240V, 50 - 60Hz <48W (On) <4W (Stand-by) <2W (Off)	
	Dimensions	<b>Net (W x H x D)</b>	400 x 390 x 171mm (15.8" x 15.4" x 6.7")
		<b>Packing (W x H x D)</b>	555 x 580 x 171mm (21.9" x 22.8" x 6.7")
Weight	<b>Net Weight</b>	6.2Kg (13.6lbs)	
	<b>Gross Weight</b>	8.0Kg (17.7lbs)	
Packing	<b>1 Pallet</b>	30 Cartons	
	<b>20' Container</b>	360 Sets	
	<b>40' Container</b>	780 Sets	

All specifications are subject to change without prior notice.